

## APC 64 66 (785 759)



Figure without obligation

- Reinforced stand-up collar
- Zip and hook-and-loop fasteners

Type	APC 64 66
Part No.	785 759
Direct incident energy ( $E_{ic}$ )	(class 2 / 7 kA, 500 ms) 423 kJ / m <sup>2</sup>
Extended direct incident energy ( $E_{ie}$ )	(class 2*) 1050 ... 1390 kJ / m <sup>2</sup>
Arc energy ( $W_{arc}$ )	318 kJ
ATPV (Arc Thermal Performance Value)	33.1 cal / cm <sup>2</sup>
Size	64 / 66
Outer material	Siliconised calf grain leather, 100% Kevlar interlock knit
Inner material	100% cotton
Material (sewing thread)	100% Kevlar
Standard	Box test according to IEC 61482-1-2, EN ISO 14116
Weight	4,4 kg
Customs tariff number (Comb. Nomenclature EU)	42031000
GTIN	4013364329362
PU	1 pc(s)

\*) The distance of the specimen was reduced from 300 mm to 150 mm based on IEC 61482-1-2.  
If the protective coat is heavily soiled, it can be dry cleaned in a leather cleaner's.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.