

APJ 48 (785 770)



Figure without obligation

- Reinforced stand-up collar
- Useful side arm pockets

| Type | APJ 48 |
|---|--|
| Part No. | 785 770 |
| Direct incident energy (E_{ic}) | (class 2 / 7 kA, 500 ms) 423 kJ / m ² |
| Extended direct incident energy (E_{ie}) | (class 2*) 1050 ... 1390 kJ / m ² |
| Arc energy (W_{arc}) | 318 kJ |
| ATPV (Arc Thermal Performance Value) | 33.1 cal / cm ² |
| Size | 48 |
| Outer material | Siliconised calf grain leather, 100% Kevlar interlock knit |
| Inner material | 100% cotton |
| Material (sewing thread) | 100% Kevlar |
| Standard | Box test in accordance with IEC 61482-1-2, EN ISO 14116 |
| Weight | 1,71 kg |
| Customs tariff number (Comb. Nomenclature EU) | 42031000 |
| GTIN | 4013364149458 |
| PU | 1 pc(s) |

*¹) The distance of the specimen was reduced from 300 mm to 150 mm based on IEC 61482-1-2.
If the protective jacket is heavily soiled, it can be dry cleaned in a leather cleaner's.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.