

**NEW** PAV 3+1 16 ZAK (758 099)



Figure without obligation

| Type  | PAV 3+1 16 ZAK   |
|---|--|
| Part No.                                      | 758 099  |
| Cable length (A / B / C)                      | 1750 mm  |
| Cable length (D)                              | 3200 mm  |
| Cable cross-section                           | 16 mm <sup>2</sup>                                     |
| Cable sheath                                  | transparent  |
| Clamping range                                | 5-25 mm  |
| Colour (clamp A / B / C)                      | black  |
| Colour (clamp D)                              | red  |
| Possible clamp operations                     | > 500  |
| Max. continuous operating current             | 10 A   |
| Operating temperature range                   | -30 °C ... +50 °C                                      |
| Storage temperature range                     | -40 °C ... +70 °C                                      |
| Cable structure                               | flexible bare stranded Cu wire according to VDE 0295-6 |
| Dielectric strength (cable sheath)            | min. 10 kV/mm  |
| Wall thickness (insulation)                   | 1.20 mm (typical)                                      |
| Insulation                                    | PVC compound TM2 according to HD21.1                   |
| Weight  | 3,06 kg  |
| Customs tariff number (Comb. Nomenclature EU) | 85369095   |
| GTIN  | 4013364287587  |
| PU  | 1 pc(s)  |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.