


DCO SD2 E 48 (917 989)


- Space-saving terminal block with integrated surge protection
- Disconnection module for disconnecting signal circuits for maintenance work
- For installation in conformity with the lightning protection zone concept at the boundaries from 1 –2 and higher



Figure without obligation



Basic circuit diagram DCO SD2 E 48



Dimension drawing DCO SD2 E 48

Finely-limiting surge protective device with disconnection function and powerful diodes to earth for two single lines sharing a common reference potential and unbalanced interfaces.

Type	DCO SD2 E 48
Part No.	917 989
SPD class	TYPE 4 PI
Nominal voltage (U_N)	48 V
Max. continuous operating voltage (d.c.) (U_C)	58 V
Max. continuous operating voltage (a.c.) (U_C)	41 V
Nominal current at 60 °C (I_n)	10 A
C1 Total nominal discharge current (8/20 μ s) (I_n)	0.3 kA
C1 Nominal discharge current (8/20 μ s) per line (I_n)	0.15 kA
Voltage protection level line-line for I_n C1 (U_p)	≤ 180 V
Voltage protection level line-PG for I_n C1 (U_p)	≤ 90 V
Voltage protection level line-line at 1 kV/ μ s C3 (U_p)	≤ 150 V
Voltage protection level line-PG at 1 kV/ μ s C3 (U_p)	≤ 75 V
Cut-off frequency line-PG (f_c)	8.7 MHz
Capacitance line-line (C)	≤ 0.35 nF
Capacitance line-PG (C)	≤ 0.65 nF
Operating temperature range (T_U)	-40 °C ... +80 °C
Degree of protection	IP 20
For mounting on	35 mm DIN rails acc. to EN 60715
Connection (input / output)	spring / spring
Cross-sectional area (solid)	0.34-2.5 mm ²
Cross-sectional area (flexible)	0.34-2.5 mm ²
Earthing via	DIN rail / terminal
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21 / EN 61643-21
Approvals	UL, CSA, SIL, EAC
SIL classification	up to SIL3 ^{*)}
Weight	30 g
Customs tariff number (Comb. Nomenclature EU)	85363010
GTIN	4013364150669
PU	1 pc(s)

^{*)} For more detailed information, please visit www.dehn-international.com.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.