

EMG METREL MI 3123 (578 351)



Figure without obligation

For all kinds of earth resistance measurement, such as the 4-conductor method (Wenner method) for measuring the soil resistivity and resistance measurements in earth termination systems.

Accessories:

- Power supply adapter + 6 batteries NiMH AA
- CD with instruction manual and handbook
- Calibration certificate for first calibration
- PC Software Euro Link Pro PLUS to ZVEH für Smartec incl. USB/RS232 cable
- Padded carrying bag and hand strap

The earthing test leads, test clamps and augers must be ordered separately.

SUCCESSOR for Part No. 578 350

Type	EMG METREL MI 3123
Part No.	578 351
Display	digital LCD
Resistance measuring range acc. to EN 61557	0.67 bis 9 999 Ω
Measuring method	earthing resistance, soil resistivity
Frequency of the test voltage	125 Hz
Measurement category	CAT IV
Enclosure material	plastic
Dimension (l x w x d)	135 x 230 x 75 mm
Weight	850 g
Customs tariff number (Comb. Nomenclature EU)	90303330
GTIN	4013364356429
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.