

## **UMG HT ET5071 (578 390)**



Figure without obligation

For low-ohm measurements and loop impedance measurement.

For testing the continuity of reinforcement steel in concrete with 10 A test current acc. to IEC/EN 62305-3.

Wtih automatic switchoff and transport bag.

Additional test functions for:

Voltage

Frequency

Impedance

Accessories:

Schuko plug on 3-phase split-plug

Kit: 3 cables + 3 alligator clamps + 1 test prod

Power cable with 10 A

2 measuring wires of 3 m each for continuity testing 10 A

2 measuring wires of 10 m each for continuity testing 10 A

Windows software + optic USB cable C2006

Туре	UMG HT ET5071
Part No.	578 390
Display	digital LC display with backlight
Resistance measuring range	0.001 to 99.9 Ω
Test current	0.2 and 10A
Test function	4 phase
Interface	optic / USB interface
Memory	999 measurements
Enclosure material	plastic
Dimension (I x w x d)	225 x 165 x 105 mm
Weight	3,88 kg
Customs tariff number (Comb. Nomenclature EU)	90303200
GTIN	4013364240582
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

© DEHN + SÖHNE GmbH + Co. KG · Hans-Dehn-Str. 1 · Postfach 1640 · D-92306 Neumarkt · Tel. +499181 906-0 · www.dehn.de