

## WJP OC L (786 743)

- Reflectors for better visibility
- Exchangeable arm and leg protectors
- Two-way zip
- Hood as accessory



Figure without obligation

Protective overall against high-pressure water jets, complete with arm and leg protectors.

| Type  | WJP OC L  |
|---|---|
| Part No.                                      | 786 743 <small>new</small>                              |
| High-pressure resistant                       | ≤ 1000 bar  |
| Size  | L   |
| Material                                      | multilayer laminate                                     |
| Type  | breathable and waterproof (class 3 according to EN 343) |
| Standards / test principles                   | EN 343, EN 13034 (type 6), GS-IFA-P15                   |
| Test parameters according to GS-IFA-P15       | flat jet nozzle type B                                  |
| – Distance (nozzle – surface of test sample)  | 7.5 cm  |
| – Angle (high-pressure water jet)             | 15 °  |
| – Speed (feed)                                | 0.5 m/s   |
| – Quantity of water (high-pressure water jet) | 22 l/min  |
| – Pressure (high-pressure water jet)          | 1200 bar*   |
| Weight  | 2,45 kg   |
| Customs tariff number (Comb. Nomenclature EU) | 62113390  |
| GTIN  | 4013364365452   |
| PU  | 1 pc(s)   |

\* The test for protection against penetration of high-pressure water jets is performed with a safety factor of 1.2.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.