

DRC LC M1+ (910 655)

- Fast testing of LifeCheck-equipped arresters
- Handheld device, easy to transport and operate
- Country-specific adapter for charging unit



Figure without obligation



Snap-on LifeCheck sensor

Portable device with LifeCheck sensor for flexible use. Fast and easy testing of LifeCheck-equipped arresters. LEDs indicate the status, charge of battery and the result of the LifeCheck test. The DRC LC M1+ features a snap-on LifeCheck sensor.

Type	DRC LC M1+
Part No.	910 655
Testing of	BLITZDUCTOR XT / XTU ML
Testing of BXT ML EX	BLITZDUCTOR XT ML EX: for use in non-hazardous atmospheres only!
Voltage supply (included in delivery)	lithium-polymer battery
RFID transmission frequency	125 kHz
Measured value indication	LED
Testing period	typically 3 to 10 sec.
Operating temperature range	-20 °C ... +60 °C
Battery test	automatically switched off in case of empty batteries
Cable length to the LifeCheck sensor	approx. 1000 mm
Dimensions of the LifeCheck sensor	90 x 51 x 12 mm
Dimensions of the hand-held device	122 x 69 x 33 mm
Delivery includes	hand-held device, BXT LifeCheck sensor, power supply unit with country-specific adapters, USB cable, test module for reference, storage case
Dimensions of the storage case	275 x 230 x 83 mm
Weight	835 g
Customs tariff number (Comb. Nomenclature EU)	90308930
GTIN	4013364149250
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.