


DG S CI 275 (952 079)


- Arrester backup fuse integrated in the protection module
- Prewired complete unit consisting of a base part and plug-in protection modules
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG S CI 275



Dimension drawing DG S CI 275

Pluggable single-pole surge arrester consisting of a base part and plug-in protection module; with integrated backup fuse; optionally available with floating remote signalling contact.

| Type Part No. | DG S CI 275 952 079 |
|--|---|
| SPD according to EN 61643-11 / IEC 61643-11 | type 2 / class II |
| Energy coordination with terminal equipment (≤ 10 m) | type 2 + type 3 |
| Nominal a.c. voltage (U_N) | 230 V (50 / 60 Hz) |
| Max. continuous operating voltage (a.c.) (U_C) | 275 V (50 / 60 Hz) |
| Nominal discharge current (8/20 μ s) (I_n) | 12.5 kA |
| Max. discharge current (8/20 μ s) (I_{max}) | 25 kA |
| Voltage protection level (U_P) | ≤ 1.5 kV |
| Voltage protection level at 5 kA (U_P) | ≤ 1 kV |
| Response time (t_A) | ≤ 25 ns |
| Max. mains-side overcurrent protection | not required |
| Rated breaking capacity of the internal backup protection | 25 kA |
| Short-circuit withstand capability (I_{SCCR}) | 25 kA _{rms} |
| Temporary overvoltage (TOV) (U_T) – Characteristic | 335 V / 5 sec. – withstand |
| Temporary overvoltage (TOV) (U_T) – Characteristic | 440 V / 120 min. – safe failure |
| Operating temperature range (T_U) | -40 °C ... +80 °C |
| Operating state / fault indication | green / red |
| Number of ports | 1 |
| Cross-sectional area (min.) | 1.5 mm ² solid / flexible |
| Cross-sectional area (max.) | 35 mm ² stranded / 25 mm ² flexible |
| For mounting on | 35 mm DIN rails acc. to EN 60715 |
| Enclosure material | thermoplastic, red, UL 94 V-0 |
| Place of installation | indoor installation |
| Degree of protection | IP 20 |
| Capacity | 1 module(s), DIN 43880 |
| Approvals | KEMA, VDE |
| Weight | 141 g |
| Customs tariff number (Comb. Nomenclature EU) | 85363030 |
| GTIN | 4013364128446 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.