


DG SE H LI 1000 FM (952 937)


- Prewired single-pole surge arrester with clear "Lifetime Indication": Three-step "Lifetime Indication" (green-yellow-red) linked with a remote signalling contact
- Prompts the user in time <YELLOW> to replace the protection module in case of imminent arrester overload --> early warning system
- The arrester is operational without derating until the protection module is replaced and is thus suited for use in condition monitoring systems



Figure without obligation



Basic circuit diagram DG SE H LI 1000 FM



Dimension drawing DG SE H LI 1000 FM

Pluggable single-pole surge arrester with three-step early warning system (green-yellow-red) comprising a base part and a plug-in protection module.

Type	DG SE H LI 1000 FM
Part No.	952 937
SPD according to EN 61643-11 / IEC 61643-11	type 2 / class II
Energy coordination with terminal equipment (≤ 10 m)	type 2 + type 3
Nominal voltage (a.c.) (U_N)	690 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) (U_C)	1000 V (50 / 60 Hz)
Nominal discharge current (8/20 μ s) (I_n)	20 kA
Max. discharge current (8/20 μ s) (I_{max})	40 kA
Voltage protection level (U_P)	≤ 4.5 kV
Voltage protection level at 5 kA (U_P)	≤ 3.5 kV
Response time (t_A)	≤ 25 ns
Max. mains-side overcurrent protection	100 A gG
Short-circuit withstand capability for max. mains-side overcurrent protection (I_{SCCR})	25 kA _{rms}
Temporary overvoltage (TOV) (U_T) – Characteristic	1205 V / 5 sec. – withstand
Temporary overvoltage (TOV) (U_T) – Characteristic	1320 V / 120 min. – safe failure
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / yellow / red
Remote signalling	activated in case of yellow indication
Number of ports	1
Cross-sectional area (min.)	1.5 mm ² solid / flexible
Cross-sectional area (max.)	35 mm ² stranded / 25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP20
Capacity	1.5 module(s), DIN 43880
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm ² solid / flexible
Weight	207 g
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364158603
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.