


## PHE 3 S (767 403)

- Easy transport due to detachable insulating stick



Type	PHE 3 S
Part No.	767 403
Nominal voltage (U <sub>n</sub> )	3 kV
Type of voltage	a.c.
Frequency	50 Hz
Total length (l <sub>c</sub> )	1115 mm
Insertion depth (l <sub>o</sub> )	320 mm
Material (indicator with test prod) (l <sub>s</sub> )	550 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	-25 °C ... +55 °C, climatic category N
Design	Complete
For use at	
For	Indoor and outdoor installations
Application	Switchgear installations and overhead lines
Design	Single-pole
Indication	Visual
Self-testing element	yes
Material (test prod)	Glass-fibre reinforced epoxy resin tube
Material (test electrode)	Copper alloy/gal Sn
Material (indicator)	Plastic, fully insulated
Material (insulating stick)	Glass-fibre reinforced polyester tube
Weight	2,15 kg
Customs tariff number (Comb. Nomenclature EU)	90303330
GTIN	4013364094024
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.