

## IS 123 SQ STK 2000 (766 322)

- For use as switching, operating and earthing stick
- Handle closed with plastic plug-in coupling for extending the handle



Figure without obligation



Figure without obligation

Type	IS 123 SQ STK 2000
Part No.	766 322
Nominal voltage (U <sub>N</sub> )	1 ... 123 kV
Max. load on the operating head <sup>1)</sup>	8 kg
Total length (l <sub>G</sub> )	2000 mm
Insulating clearance (l <sub>I</sub> )	1300 mm
Handle length (l <sub>H</sub> )	500 mm
Insertion depth (l <sub>O</sub> )	200 mm
Standard (insulating stick)	E DIN VDE V 0681-1
For	Indoor and outdoor installations
Material	Glass-fibre reinforced polyester tube
Diameter	30 mm
For use at	*
Supporting head for	T pin shaft
Anti-rotation plug-in coupling including end fitting	Yes
Type of device	Insulating stick
Weight	800 g
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364134256
PU	1 pc(s)

<sup>1)</sup> Max. shutter weight when inserting insulating protective shutters

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.