

# Earthing and Short-Circuiting Devices (partly insulated) for Low-Voltage Cable Distribution Cabinets

## Accessories

### EKV3 35TI HK VDZ2VDX (VDZ2VDX)

For installation of earth clamps EK I FL20 DGF or EK FL20 FS.

For cable distribution cabinets.



Type	EKV3 35TI HK VDZ2VDX
Part No.	VDZ2VDX
Version	Three-pole
Cable cross-section (phase side)	35 mm <sup>2</sup>
Cable cross-section (earth side)	35 mm <sup>2</sup>
Cable cross-section Cu	35/35 mm <sup>2</sup>
Length of phase cable A	200 mm
Length of phase cable B	400 mm
Length of phase cable C	600 mm
Length of earthing cable	500 mm
Fully insulated	No
Max. short-circuit current I <sub>k</sub> 0.5 s	10.0 kA
Max. short-circuit current I <sub>k</sub> 1 s	6.9 kA
Connection on the phase conductor	M10 bolts
Material (bolts)	Copper alloy / gal Sn
Temperature range	-25 °C ... +55 °C
Weight	1,38 kg
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364163843
PU	1 pc(s)

Note: When ordering, please specify a clear Variant No.