

Earthing and Short-Circuiting Devices (partly insulated) for Low-Voltage Cable Distribution Cabinets

Accessories

EKV3 16TI EK VSB29AH (VSB29AH)

Clamping range up to 24 mm and fixing via adjustable handle DGF EKV VI.
Screw-on cable lugs with M10 hexagon pin on the phase cable end.
To be screwed onto earthing cartridges with M10 connection of service entrance boxes.



Type	EKV3 16TI EK VSB29AH
Part No.	VSB29AH
Version	Three-pole
Cable cross-section (phase side)	16 mm ²
Cable cross-section (earth side)	16 mm ²
Cable cross-section Cu	16/16 mm ²
Length of phase cable A	190 mm
Length of phase cable B	140 mm
Length of phase cable C	140 mm
Length of earthing cable	280 mm
Fully insulated	No
Max. short-circuit current I _k 0.5 s	4.5 kA
Max. short-circuit current I _k 1 s	3.2 kA
Connection on the phase conductor	M10 bolts
Material (bolts)	Copper alloy / gal Sn
Temperature range	-25 °C ... +55 °C
Weight	805 g
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364162662
PU	1 pc(s)

Note: When ordering, please specify a clear Variant No.