

## BEV OL PF PKW R (750 217)



Figure without obligation

Figure without obligation

Kit includes:		
Type	Part No.	Pos. No.
Tommy bar (K) or ratchet (R)		
EKV K H 50 12000	2x 751 121	<b>1+4+8+11</b>
EKV R H 50 12000	2x 751 122	<b>1+5+8+11</b>
EST SQL RW 4915 TA	2x 769 506	<b>14</b>
STT 55 27 30	1x 785 111	<b>17</b>

Type	BEV OL PF PKW R
<b>Part No.</b>	<b>750 217</b>
Design	Ratchet
Type of cable	Single-pole
Cable cross-section (phase side)	50 mm <sup>2</sup>
Cable cross-section (earth side)	50 mm <sup>2</sup>
Length (single-pole cable)	12000 mm
Fully insulated	No
Cable length	12000 mm
Standard	EN/IEC 61230 (DIN VDE 0683-100)
Max. short-circuit current I <sub>k</sub> 0.06 s	34.0 kA
Weight	17,08 kg
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364157262
PU	1 pc(s)

<sup>1)</sup> Profile-free earthing means that the earthing cable can be suspended at the tower, thus allowing for limited diesel locomotive operation.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.