

BEV OL PF PKW K (750 200)



Figure without obligation

Figure without obligation

Kit includes:		
Type	Part No.	Pos. No.
Tommy bar (K) or ratchet (R)		
EKV K H 50 12000	2x 751 121	1+4+8+11
EKV R H 50 12000	2x 751 122	1+5+8+11
EST SQL RW 4915 TA	2x 769 506	14
STT 55 27 30	1x 785 111	17

Type	BEV OL PF PKW K
Part No.	750 200
Design	Tommy bar
Type of cable	Single-pole
Cable cross-section (phase side)	50 mm ²
Cable cross-section (earth side)	50 mm ²
Length (single-pole cable)	12000 mm
Fully insulated	No
Cable length	12000 mm
Standard	EN/IEC 61230 (DIN VDE 0683-100)
Max. short-circuit current I _k 0.06 s	34.0 kA
DB drawing No.	3 Ebgw 01.67
Weight	16,95 kg
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364123830
PU	1 pc(s)

¹⁾ Profile-free earthing means that the earthing cable can be suspended at the tower, thus allowing for limited diesel locomotive operation.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.